

Amendments to the Claims:

The following listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) An electromagnetic relay (1)-comprising:

- a base comprising at least one printed circuit card-(2), which card has at least two conductor tracks (4a; 4b; 4c)-forming respective switch accesses;
- at least one conductive contact element (10)-movable between a closed position in which it presses against said two conductor tracks in order to establish an electrical connection between them, and an open position in which the contact element is spaced apart from at least one of said two tracks;
- a contact element support-(13), the support comprising at least one flexible arm (21) carrying the contact element-(10); and
- an actuator (3)-mounted on the printed circuit card, and comprising at least one coil (30)-constituted by a winding of electric wires;

wherein ~~the relay being characterized by the fact that~~ the support (13)-includes at least one portion, in particular a portion in the form of a tongue-(25), on which a moving member of the actuator acts in order to move said flexible arm (21)-of the support.

2. (Currently Amended) A relay according to claim 1, wherein ~~characterized by the fact that~~ the support (13)-is made of a conductive material and carries an insulating block (11)-to insulate the contact element (10)-from the support-(13).

3. (Currently Amended) A relay according to claim 2, wherein ~~characterized by the fact that~~ the contact element ~~element~~-(10) comprises a conductive layer deposited on a first face of the

insulating block ~~(11)~~, which block is secured to the support ~~(13)~~ via a second face that is opposite from the first face.

4. (Currently Amended) A relay according to claim 2, ~~wherein~~ characterized by the fact that the contact element ~~(10)~~ is constituted by a conductive blade ~~(43)~~ and ~~wherein~~ by the fact that the insulating block ~~(44)~~ is obtained by overmolding on the support and the blade.

5. (Currently Amended) A relay according to claim 1, ~~wherein~~ characterized by the fact that the support ~~(13)~~ is made of an insulating material.

6. (Currently Amended) A relay according to claim 5, ~~wherein~~ characterized by the fact that the contact element ~~(10)~~ comprises a conductive layer ~~(45)~~ deposited on a region of the support ~~(13)~~.

7. (Currently Amended) A relay according to ~~any preceding claim 1, wherein,~~ characterized by the fact that the support ~~(13)~~ includes at least one portion ~~(14)~~ that is rigidly secured to a stationary portion ~~(15)~~ of the relay.

8. (Currently Amended) A relay according to ~~to any preceding claim 1, wherein,~~ characterized by the fact that the support ~~(13)~~ carries a plurality of contact elements ~~(10)~~, each associated with two switch accesses of the printed circuit card.

9. (Currently Amended) A relay according to ~~any preceding claim 1, wherein,~~ characterized by the fact that the moving member comprises an armature ~~(31)~~ suitable for pivoting about an axis ~~(Y)~~ parallel to the plane of the printed circuit card.

10. (Currently Amended) A relay according to ~~any preceding claim 1, wherein, characterized~~
~~by the fact that~~ the support (13) is made as a single piece.

11. (Currently Amended) A relay according to ~~any preceding claim 1, wherein, characterized~~
~~by the fact that~~ the printed circuit card (2) has at least one electrical power supply conductor
track (8a-8d) electrically connected to said at least one coil (30).

12. (Currently Amended) A relay according to claim 11, ~~wherein characterized by the fact that~~
said connection is implemented via a connection member (39) fastened in a hole (9) in the
printed circuit card.

13. (Currently Amended) A relay according to claim 12, ~~wherein characterized by the fact that~~
the connection member (39) comprises a pin with a slot (40) in which a terminal (36) of the
coil (30) can engage.

14. (Currently Amended) A relay according to ~~to any preceding~~ claim 1, wherein,
~~characterized by the fact that~~ the base comprises a plurality of printed circuit cards (61) that
are stacked on one another and fastened together.

15. (Currently Amended) A relay according to claim 14, ~~wherein characterized by the fact that~~
the conductor tracks (62) of the card are interconnected by plated-through holes (63) made
through the thickness of at least one of the cards.

16. (Currently Amended) A relay according to ~~any preceding~~ claim 1, wherein,
~~characterized by the fact that~~ at least one of the conductor tracks (4a-4c; 8a-8d) is connected
to a conductive strip (5) extending across the thickness of the printed circuit card.

17. (Currently Amended) A relay according to claim 16, ~~wherein~~ characterized by the fact that
said conductive strip (5) is made on an edge face of the printed circuit card (2), being
constituted in particular by a metal-plated surface in a setback (6) in the edge face of the
printed circuit card.

18. (Currently Amended) A relay according to claim 16, ~~wherein~~ characterized by the fact that
the conductive strip (5) is constituted by the metal-plated wall of a hole in the printed circuit
card.

19. (Currently Amended) A relay according to ~~claim any one of claims 1, wherein to 16,~~
~~characterized by the fact that~~ at least one of the conductor tracks (4a-4c; 8a-8d) is connected
to a socket (70) enabling a coaxial cable or a coaxial connector to be connected thereto.

20. (Currently Amended) A relay according to ~~any preceding claim 1, wherein,~~ characterized
~~by the fact that~~ the printed circuit card (2) is made on the basis of glass epoxy or of ceramic.

21. (Currently Amended) A relay according to ~~any preceding claim 1, including,~~ characterized
~~by the fact that it includes~~ a cover (40) secured to the printed circuit card, in particular by
adhesive.

22. (Currently Amended) A relay according to ~~any preceding claim 1, wherein, characterized~~
~~by the fact that~~ the coil (30) is separate from the card (2).

23. (Currently Amended) A method of manufacturing an electromagnetic relay as defined in
~~any preceding claim 1, the base comprising a plurality of printed circuit cards that are stacked~~
~~on one another and fastened together, the method comprising being characterized by the fact~~
~~that it comprises~~ the following steps:

- cutting out a plurality of printed circuit cards;
- etching conductor tracks on the cards;
- stacking the printed circuit cards; and
- firing the stack of cards.